

晶采光電科技股份有限公司 AMPIRE CO., LTD.

Specifications for LCD module

Customer	
Customer part no.	
Ampire part no.	AM-1280800QTZQW-T02H
Approved by	
Date	J C C C C C C C C C C C C C C C C C C C

□ Approved For Specifications

□Approved For Specifications & Sample

AMPIRE CO., LTD.

Date: 2018/2/23

4F., No.116, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City221, Taiwan (R.O.C.)

新北市汐止區新台五路一段 116號 4樓(東方科學園區 A棟)

TEL:886-2-26967269 , FAX:886-2-26967196 or 26967270

Approved by	Checked by	Organized by
Palk	Camp	Kokan

RECORD OF REVISION

Revision Date	Page	Contents	Editor
2017/8/17		New Release	Emil
2018/2/23		Add Power consumption	Kokai
	ADVA	ANCED ELECTRONIC SYS	STEMS

1. GENERAL DESCRIPTION

The screen format is intended to support 1280(H) x 800(V) screen and 16.7M (RGB 8-bits)

1.1 Display Characteristics

The following items are characteristics summary on the table under 25 °C condition:

Item	Specifications	unit
Screen Diagonal	12.1	inch
Display resolution(dot)	1280 (RGB) x 800	dots
Display area	261.12 (W) x 163.2 (H)	mm
Pixel pitch	0.204(W) x 0.204 (H)	mm
Color configuration	R.G.B Vertical stripe	
Overall dimension	298.0(W) x 204.0(H) x 15.475(D)	mm
Display Mode	SFT, Normally Black	
Brightness	383	cd/m ²
Backlight unit	LED	
Display color	16.7M	colors
Electri <mark>cal T</mark> rea <mark>tmen</mark> t	1 chan <mark>nel L</mark> VDS	

Note(1) Viewing direction for best image quality is different from TFT definition; there is a 180 degree shift.

Note(2) Requirements on Environmental Protection: Q/S0002 | C SYSTEMS

Note(3) LCM weight tolerance : \pm 5%

2. Input/output Terminals

2.1 TFT LCD Panel

Mating Connector: 093G30-B0001A-G4 (Starconn) or compatible

Mating	Connector: 093	<u>G30-B</u>	30001A-G4 (Starconn) or compatible			
12	Name	I/O	Description			
1	VLED	Р	Backlight power supply +12V			
2	VLED	Р	Backlight power supply +12V			
3	VLED	Р	Backlight power supply +12V			
4	VLED	Р	Backlight power supply +12V			
5	VLED_EN	Р	Backlight on/off control			
6	VLED_PWM	Р	Backlight dimming control			
7	GND	Р	Power ground			
8	GND	Р	Power ground			
9	VDD	Р	Power Supply +3.3V			
10	VDD	Р	Power Supply +3.3V			
11	GND	Р	Power ground			
12	GND	Р	Power ground			
13	Rxin0-	I	-LVDS differential data input(R0~R5,G0)			
14	Rxin0+	I	+LVDS differential data input(R0~R5,G0)			
15	GND	Р	Power ground			
16	Rxin1-	ı	-LVDS differential data input(G1~G5,B0~B1)			
17	Rxin1+	ı	+LVDS differential data input(G1~G5,B0~B1)			
18	GND	Р	Power ground			
19	Rxin2-		-LVDS differential data input(B2∼B5,-,-,DE)			
20	Rxin2+	יעור	+LVDS differential data input(B2~B5,-,-,DE)			
21	GND	Р	Power ground			
22	RxCLK-	I	-LVDS differential data input			
23	RxCLK+	I	+LVDS differential data input			
24	GND	Р	Power ground			
25	Rxin3-	I	-LVDS differential data input(R6~R7,G6~G7,B6~B7)			
26	Rxin3+	l	+LVDS differential data input(R6~R7,G6~G7,B6~B7)			
27	GND	Р	Power ground			
28	NC	-	No Connection			
29	GND	Р	Power ground			
30	GND	Р	Power ground			
Noto: I	/∩ definition:					

Note: I/O definition:

I-----Input P----Power/Ground

3 Absolute Maximum Ratings

3.1 Driving TFT LCD Panel

GND=0V

Item	Symbol	MIN	MAX	Unit	Remark
Voltage Input	Vin	-0.5	5.0	V	Note1
Operation Temperature	TOP	-20	70	$^{\circ}$ C	
Storage Temperature	TST	-30	80	$^{\circ}$ C	
	RH		≦95	%	Ta≦40°ℂ
			≦85	%	40°C <ta≦50°c< td=""></ta≦50°c<>
Relative Humidity (Note2)			≦55	%	50°C <ta≦60°c< td=""></ta≦60°c<>
			≦36	%	60°C <ta≦70°c< td=""></ta≦70°c<>
			≦24	%	70°C <ta≦80°c< td=""></ta≦80°c<>
Absolute Humidity	AH		≦70	g/m ³	Ta>70°ℂ

Table 3.1 absolute maximum rating

Note(1) Input voltage include Rxin0-/+, Rxin1-/+, Rxin2-/+, Rxin3-/+, RxCLK-/+, SEL6/8, VDD.

Note(2) Ta means the ambient temperature. It is necessary to limit the relative humidity to the specified temperature range. Condensation on the module is not allowed.

4. ELECTRICAL CHARACTERISTICS

4.1 Driving TFT LCD Panel

Date: 2018/2/23

VDD=3.3V,GND=0V, Ta=25°C

Item	Symbol	Min	Тур	Max	Units	Remark	
Power supply '	Voltage	VDD	3.0	3.3	3.6	V	
Power supply	ripple	V_{P-P}	-	-	100	mV	
Power supply	current	I _{DD}	-	660	-	mA	
Power consu	mption	Р	-	2178	-	mW	Note 1
Differential input voltage		Vid	200	-	600	mV	
Differential input con	Differential input common voltage		-	1.2	-	V	
Differential input	Low level	VTL	-100	-	1	mV	
threshold voltage	High level	VTH		ı	100	mV	
Inrush Cur	rent	I _{rush}			1.5	Α	

Table 4.1 LCD module electrical characteristics




Fig 4.1 LVDS characteristics

Note(1) To test the current dissipation, using the "white pattern" shown.

4.2 Driving Backlight

Date: 2018/2/23

Input signals shall be low or Hi-Z state when VDD is off.

Item	Symbol	Min.	Тур.	Max	Unit	Remark	
Backlight power supply vol	VLED	10	12	15	V		
Backlight power supply cur	rent	ILED	-	600	-	mΑ	
Backlight power consump	tion	PLED	-	7200	-	mW	
Input voltage for VLED_PWM	High level	-	2.0	1	5.0	V	
signal	Low level	-	0	ı	0.4	>	
Input voltage for VLED EN	High level	-	2.0	ı	5.0	>	
input voltage for VLED_EN	Low level	-	0	ı	0.4	>	
VLED_PWM frequency	Fpwm	200	-	20K	Hz		
VLED_PWM duty	D	1	-	100	%	Note 1	
Operating Life Time		-	50000	-	-	hrs	Note 2

- Note(1) According to LED driver IC characteristics, the minimum value of VELD_PWM duty may vary with VLED_PWM frequency, higher the frequency, bigger the duty.
- Note(2) Optical performance should be evaluated at Ta=25° only.
- Note(3) If LED is driven by high current, high ambient temperature & humidity condition.

 The life time of LED will be reduced.
- Note(4) Operating life means brightness goes down to 50% of initial brightness. Typical operating life time is estimated data. CTRONIC SYSTEMS

5 Timing Chart

5.1 LVDS signal timing characteristics

VDD=3.3V, GND=0V, Ta=25℃

Parameter	Symbol	Min	Тур	Max	Unit
CLK frequency	1/t _C	67	71	75	MHz
Horizontal display area	thd	-	1280	-	tc
Horizontal period	th	1290	1440	-	tc
Vertical display area	tvd	-	800	-	th
Vertical period	tv	810	823	-	th
Frame Rate	F	-	60	-	HZ

5.2 Input Clock and Data timing Diagram:




Figure 5.2 Input signal data timing

5.3 LVDS data input format

8-bit mode data input




Figure 5.3 LVDS data input format

5.4 Power On/Off Sequence

Item	Symbol	Min	Тур	Max	Unit
VDD on to VDD stable	Tp1	0.5	-	10	ms
VDD stable to signal on	Tp2	0	ı	50	ms
Signal on to VLED_EN on	Tp3	200		1	ms
PWM on to VLED_EN on	Tp4	0	-	200	ms
VLED to PWM on	Tp5	10	1		ms
VLED on to VELD stable	Tp6	0.5	ı	10	ms
VDD off time	Tp7	0	1	10	ms
VDD off to next VDD on	F Tp8 R	500	S	VSTF	ms
Signal off before VDD off	Tp9	0)	50	ms
VLED_EN off before signal off	Tp10	200	ı	ı	ms
VLED_EN off before PWM off	Tp11	0	-	200	ms
PWM off before VLED off	Tp12	10	-	-	ms

Table 5.4 Power on/off sequence




Figure 5.4 Interface power on/off sequence

6 Optical specification

6.1 Optical characteristic of the LCD


Item		Symbol	Condition	Min.	Тур.	Max.	Unit	Remark
		θТ		75	85			
) /i	View Angles		CD > 10	75	85		D	N-4- 0
View Ang	ies	θL	CR≧10	75	85		Degree	Note 2
		θR		75	85			
Contrast F	Ratio	CR	θ=0°	800	1000			Note 1 Mote 3
		T _{ON}			12			Note 1
Response	Time	T _{OFF}	25 ℃		13		ms	Note 4
	White	Х		0.236	0.313	0.363		
	VVIIILE	Υ		0.279	0.329	0.379		
	Red	X						
Chromaticity	- 100	Y	Backlight					Note 1
	Green	X	is ON					Note 5
	Blue	X						
Uniform	ity	U		70	75		%	Note 1 Note 6
NTSC					50		%	Note 5
Luminan	ADV	AŅCI	ED ELI	306	383		Cd/m ²	Note 1 Note 7

Test Conditions:

- 1. The ambient temperature is $25 \pm 2\,^{\circ}\text{C}$.humidity is $65 \pm 7\%$
- 2. The test systems refer to Note1 and Note 2.

Note(1) Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Note(2) Definition of viewing angle range and measurement system.

viewing angle is measured at the center point of the LCD by CONOSCOPE

(ergo-80)。




Fig. 1 Definition of viewing angle

Note(3) Definition of contrast ratio

 $Contrast\ ratio(CR) = \frac{Luminance\ measured\ when\ LCD\ is\ on\ the\ "White"\ state}{Luminance\ measured\ when\ LCD\ is\ on\ the\ "Black"\ state}$


"White state ": The state is that the LCD should drive by V_{white}.

"Black state": The state is that the LCD should drive by V_{black}.

V_{white}: To be determined V_{black}: To be determined.

Note(4) Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



- Note(5) Definition of color chromaticity (CIE1931)

 Color coordinates measured at center point of LCD.
- Note(6) Definition of Luminance Uniformity

 Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.




Fig. 2 Definition of uniformity

Lmax: The measured maximum luminance of all measurement position. Lmin: The measured minimum luminance of all measurement position.

12

Note(7) Definition of Luminance:

Measure the luminance of white state at center point.

7 Projected capacitive-type touch panel specifications

7.1 Basic Characteristic

ITEM	SPECIFICATION				
Type	Projective Capacitive Touch Panel				
Activation	Two-fingers or Single-finger				
X/Y Position Reporting	Y Position Reporting Absolute Position				
Touch Force No contact pressure required					
Calibration	No need for calibration				
Report Rate	Approx. 80 points/sec				
Control IC	ILI2511				
Conductive susceptibility 10V/m					
Water immunity					

7.2 Electrical Absolute Max Rating

Item	Symbol	Value		Unit	Note	
item	Symbol	Min.	Max.	Oill	Note	
Power supply voltage	VIN	-0.3	5.5	V	GND=0V	

7.3 ELECTRICAL CHARACTERISTICS

Specify the normal operating condition (PGND=0V)


ltem DVAN	Symbol	Min.	Тур.	Max.	Unit	Note
Power supply voltage	VIN	-	5	-	V	

7.4 Interface

CN6				
Pin No.	Symbol	Function		
1	GND	Ground		
2	DA-	USB Data-		
3	DA+	USB Data+		
4	VIN	Power supply		
5	NA	NC		
6	NA	NC		

TP needs to work in environment with stable stray capacitance. In order to minimize the variation in stray capacitance, all conductive mechanical parts must not be floating.

Intermittent floating any conductive part around the touch sensor may cause significant stray capacitance change and abnormal touch function. It is recommended to keep all conductive parts having same electrical potential as the GND of the touch controller module.



GND1, GND2 and GND3 should be connected together to have the same ground



8 Reliability Test Items

Date: 2018/2/23

Test Item	Test Conditions	Note
High Temperature Operation	Ts = 70°C , t=240 hrs	
Low Temperature Operation	Ta = -20°C , t=240 hrs	
High Temperature Storage	Ta = 80°C , t=240 hrs	1,2
Low Temperature Storage	Ta = -30°C , t=240 hrs	1,2
Storage at High Temperature and Humidity	Ta = 60°C, 90% RH , 240 hrs	1,2
Thermal Shock Test	-30°C (30min) ~ 80°C (30min) Change time:5min, 100 cycles	1,2
Vibration Test (Packing)	Frequency range:10~55Hz, Stroke:1.5mm Sweep:10Hz ~ 55Hz ~ 10Hz 2hours for each direction of X.Y.Z (6 hours total)	2

- Note(1) Ts is the temperature of panel's surface.
- Note(2) Ta is the ambient temperature of sample.
- Note(3) The module shouldn't be tested more than one condition, and all the test conditions are independent.

Note(4) All the reliability tests should be done without protective film on the module.



9 USE PRECAUTIONS

9.1 Handling Precautions

- (1) The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.
- (2) If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.
- (3) Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.
- (4) The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.
- (5) If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:
 - Isopropyl alcohol
 - Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer.


Especially, do not use the following:

Water

Ketone

Aromatic solvents

(6) Do not attempt to disassemble the LCD Module.



- (8) To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.
- (9) Be sure to ground the body when handling the LCD Modules.
- (10) Tools required for assembly, such as soldering irons, must be properly ground.
- (11) To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.
- (12) The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

9.2 Storage Precautions

- (1) When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.
- (2) The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:


 Temperature: 0°C ~ 40°C Relatively humidity: ≤80%
- (3) The LCD modules should be stored in the room without acid, alkali and harmful gas.

9.3 Transportation Precautions

(1) The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

9.4 Mechanical

(1) Please hold the LCD module properly when you use or store it.



9.5 Other

- (1) AMIPRE will provide one year warrantee for all products and three months warrantee for all repairing products.
- (2) Do not keep the LCD at the same display pattern continually. The residual image will happen and it will damage the LCD. Please use screen saver.

10. OUTLINE DIMENSION

