
VUE-2150

15.0" Square Touch Panel Mount Monitor




Features

- 15.0" active screen size (Square)
- Full-flat cover glass for extremely simple surface design
- Built-in multiple I/O interfaces for diverse media connectivity
- Adopts industrial-grade components for guaranteed performance
- Mount with multi-way and easy to extend peripheral devices (box PC/camera...)
- Front IP65 water-proof rating and IK08 high-level impact protection
- Support 10-point touch function (PCAP techology)
- Excellent noise immunity well-suited for rugged applications (CS 10V)
- Support many touch method including fingers, glove, and stylus

Specifications

Drand			Advantage
Brand	Active Coreen Circ		Advantech 15.0 inch
	Active Screen Size		
	Aspect Ratio		4:3 (Square)
	Resolution		1024 x 768 (XGA)
	Pixel Pitch		0.297(H) x 0.297(W)
Display	Brightness		500nits (LCM panel, typ.)
	Display Colors		16.7M
	Contrast Ratio		2500:1 (Typ)
	Viewing Angle		88° / 88° / 88° / 88°
	Response Time		18ms
	Backlight Life (hours)		50,00 (TW) LECTRONIC SYSTEMS
Touch	Touch Type		Projected Capacitive Touch (PCAP)
	Touch Function		10 points
	Touch Interace		USB typeB
	Touch Method		Finger/Glove/Stylus
	Stylus Pen		Active Stylus (optional accessory)
	Input	Video	VGA x 1, HDMI x 1, DisplayPort x 1
		Audio	Audio line in x 1
		Control	D-SUB-9 x 1 for external Function key
Connectivity		Other slots/ports	USB typeB 3.0 x 1 (for touch function)
	Output	Video	N/A
		Audio	3W+3W Internal Speaker
		Control	N/A
System	OSD Language		English, Simplified Chinese, Traditional Chinese
	OSD Function		Hot key (AUTO/UP/DOWN/MENU)
	Power Type		External Adapter, AC to DC, 12V
Power	Power Input-AC		100-240V _{AC} , 50-60Hz, 1.5A
	Power Consumption		18W (Typ.)
	Operating Storage	Temperature	-20°C ~ 60°C
Environment		Humidity	10% to 85% (non-condensing)
Limitoni		Temperature	-20°C ~ 60°C
		Humidity	5% to 80% (non-condensing)
	Housing Material		1.0 mm steel metal (Black), Aluminium bezel
	Waterproof Rating		Front IP65
	VESA Compatibility		100 x 100 mm
	Side mount screw hole		75 mm for bracket installation
Mechanical Specification	Hand Hoder/Stand		Stand (optional accessory)
meenanical opecinication	Cable Management		Yes, with cable organizer kit
	Dimensions	Physical without stand	359.1 x 285 x 46.2 mm
	(W x H x D)	Packing	483 x 375 x 195 mm
	Weight	Net	3.5Kg
		Gross	5.5Kg
	Installation rotation		Landscape/Portrait
Installation	Mounting on a wall		100 x 100 mm, VESA grid
	Mounting with stand/arm		100 x 100 mm, VESA grid
	Mounting through bracket		75 mm, Side mount screw hole
	Extending PC/peripherals		75 mm, Side mount screw hole
Certificate			IEC/EN 60950+62368, UL62368, BSMI, CCC, CE, FCC, UKCA
Warranty			2-year warranty (1-year for panel)



Ordering Information

Part Number	Description	Packing List
VUE-2150-XA50PA-N4	Advantech 15.0" XGA Panel Mount Monitor (incl. Japan and Korea Power Cord)	Power Adapter (1.5M, Black) Power cord (1.8M, Black) VGA cable (1.8M, Black) HDMI cable (1.8M, Black) DisplayPort cable (1.8M, Black) Audio cable (1.8M, Black) USB cable (1.8M, Black), for touch function External control key pad Side mount bracket kit Cable organizer kit (Aluminum) Startup manual (Paper)
VUE-2150-XA50PC-N4	Advantech 15.0" XGA Panel Mount Monitor (incl. China Power Cord)	
VUE-2150-XA50PX-N4	Advantech 15.0" XGA Panel Mount Monitor (incl. Europe, Taiwan, UK, and US Power Cord)	

Optional Accessories

Part Number	Description
960T-A15DEE-B0	Active Stylus Pen for VUE-2000 series, Black