VUE-2156 Series 15.6" Panel Mount Monitor



Features


- 15.6" active screen size
- 6-axis color adjustment (Green/Red/Blue/Cyan/Magenta/Yellow) for high level and more accuracy customized image
- Full-flat cover glass for extremely simple and elegant surface design
- Anti-glare (AG) treatment on screen for comfortable viewing experience
- Built-in multiple I/O interfaces for diverse media connectivity
- Adopts industrial-grade components for guaranteed performance
- Mount with multi-way and easy to extend peripheral devices (box PC/camera...)
- Front IP65 water-proof rating and IK08 high-level impact protection

(for PCAP touch model)

- Support 10-point touch function (PCAP technology)
- Excellent noise immunity well-suited for rugged applications (CS 10V)
- Support many touch method including fingers, glove, and stylus

Specifications

Model			PCAP touch None touch	
Brand			Advantech Notice touch	
Display	Active Screen Siz		15.6 inch	
	Resolution	е	1920 x 1080 (FHD)	
	Brightness		450 nits (LCM panel, typ.)	
	Contrast Ratio		800:1 (Typ.)	
	Aspect Ratio		16:9	
	Viewing Angle	<u>∧ D\/∧</u>	85°/85°/85°/85° ECTRONIC SYSTEMS	
	Response Time	ADVA	25.ms (Typ.) ELECTRONIC SYSTEMS	
	Backlight Life (ho	urs)	50,000 (Typ.)	
Touch	Touch Type		Projected Capacitive Touch (PCAP) N/A	
	Touch Function		10 points N/A	
	Touch Interface		USB N/A	
		Video	VGA x 1, HDMI x 1, DVI-D x 1, DisplayPort x 1	
	Input	Audio	Audio line in x 1	
	Input	Control	USB typeB 3.0 x 1 (for touch function)	
Connectivity		Others	USB typeA 3.0 x 2	
		Video	N/A	
	Output	Audio	2W+2W Internal Speaker	
		Control	N/A	
Control	OSD Function		Hot key (ON/OFF, LIFT, RIGHT, MENU, AUTO)	
COILLIOI	OSD Language		English, French, Korea, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese	
	Power Type		External AC to DC power adapter, 20V, 45W	
Power	Power Input		100-240V _{AC} , 50-60Hz, 2.25A	
	Power Consumpt	ion	ON: <35W; SLEEP: <0.5W; OFF: <0.3W	
Environment	Operating	Temperature	0°C-+40°C	
	Operating	Humidity	10% to 85% (non-condensing)	
	Ctorogo	Temperature	-25°C ~ 55°C	
	Storage	Humidity	5% to 93% (non-condensing)	
Mechanical Specification	Housing Material		1.0 mm sheet metal (Black)	
	VESA Compatibil	ity	100 x 100 mm	
	Dimensions	Physical	385 x 237 x 49 mm	
	(W x H x D)	Packing	455 x 330 x 185 mm	
	,	Net	3.1 Kg	
	Weight	Gross	4.7 Kg	
Installation	Mounting on a w		100 x 100 mm, VESA grid	
	Mounting with st		100 x 100 mm, VESA grid	
	Mounting through bracket		64 mm, Side mount screw hole	
Approbation	Certificates		IEC/EN 60950+62368, UL62368, CE, FCC, UKCA, CCC, BSMI	
Warranty			2-year (1-year for panel)	
			1 - Jan (- Jan Emis)	



Ordering Information ADVANCED ELECTRONIC SYSTEMS

Part Number		Description	Packing List
PCAP touch model	None touch model		
VUE-2156-FD45PA-N4	VUE-2156-FD45MA-N4	Advantech 15.6" Full HD Panel Mount Monitor (incl. Japan, Korea, Australia, and Middle East Power Cord)	Power Cord (1.5M, Black) Power Adaptor (1.5M, Black) VGA Cable (1.5M, Black) HDMI Cable (1.5M, Black) DisplayPort Cable (1.5M, Black) DVI Cable (1.5M, Black) USB Cable (1.8M, Black), for touch, PCAP model only Audio Cable (1.5M, Black) Side Mount Bracket kit Startup Manual (Paper)
VUE-2156-FD45PC-N4	VUE-2156-FD45MC-N4	Advantech 15.6" Full HD Panel Mount Monitor (incl. China Power Cord)	
VUE-2156-FD45PX-N4	VUE-2156-FD45MX-N4	Advantech 15.6" Full HD Panel Mount Monitor (incl. Europe, Taiwan, UK and US Power Cord)	

Optional Accessories

Part Number	Description
960T-A15DEE-B0	Active Stylus Pen for VUE-2000 series, Black
960T-SD-10H10-L	Desktop Stand for VUE-2000, VESA100x100, Large, support up to 7kg